


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 710/60 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	708	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1820	<b>RIM ALT</b>	DW 23 B
<b>SLR (MM)</b>	794	<b>ECE</b>	E11-106R-004520
<b>RC (MM)</b>	5447	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3075	3580	4080	4585	5090	5595
FROM 65 TO 40	3380	3935	4485	5040	5595	6150
30	3445	4010	4570	5140	5705	6270
20	3515	4090	4660	5240	5815	6395
10	3715	4325	4930	5540	6150	6765
*UPTO 10 CYC WITH FRONT LOADER	4730	5505	6275	7055	7830	8610
10HT	3445	4010	4570	5140	5705	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.