


EARTHMAX SR 22



| | |
|---------------------|--|
| | 17.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | GREYDER / YÜKLEYICI / DOZER / YÜKLEYICI / DOZER / GREYDER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| | 153 A8 ; 176 A2 |

UNDEFINED IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1350 | TRA CODE | G2/L2 |
| SLR (MM) | 590 | STAR RATING | ★ |
| RC (MM) | 3950 | | |
| RIM REC | 14.00/1.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 40 | 1850 | 2120 | 2360 | 2650 | 2900 | 3075 | 3350 | 3650 | - | - | - | - | - |
| 10 | - | - | - | - | - | - | - | - | 6000 | 6150 | 6500 | 6700 | 7100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.