

# AGRIMAX V-FLECTO

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | VF 280/70 R 18                                                                           |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| VERSION      | STANDARD                                                                                 |
| TYRE TYPE    | TL                                                                                       |
| LI/SS        | 116 D                                                                                    |



## DIMENSIONS IS STANDARD

|          |      |         |                  |
|----------|------|---------|------------------|
| SW (MM)  | 274  | RIM REC | W 9              |
| OD (MM)  | 849  | RIM ALT | 9                |
| SLR (MM) | 375  | ECE     | E11-106R-0010341 |
| RC (MM)  | 2515 | SRI     | 400              |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR                     | 0.6 | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------------------------|-----|------|------|------|------|------|
| 70                             | 620 | 725  | 825  | 930  | 1030 | 1135 |
| FROM 65 TO 40                  | 685 | 800  | 910  | 1025 | 1135 | 1250 |
| 30                             | 700 | 815  | 930  | 1045 | 1160 | 1275 |
| 20                             | 715 | 830  | 945  | 1065 | 1180 | 1300 |
| 10                             | 755 | 880  | 1000 | 1125 | 1250 | 1375 |
| *UPTO 10 CYC WITH FRONT LOADER | 960 | 1120 | 1275 | 1435 | 1590 | 1750 |
| 10HT                           | 700 | 815  | 930  | 1045 | 1160 | 1275 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.