


AGRIMAX RT 657

TIRE SIZE	540/65 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	149 D ; 152 A8



DIMENSIUNI IS STANDARD

SW (MM)	530	RIM REC	W 16 L
OD (MM)	1413	RIM ALT	W 18 L
SLR (MM)	643	ECE	E4-106R-000650
RC (MM)	4253	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1560	1820	2050	2275	2505	2700	2990	3250
50	1640	1915	2155	2395	2630	2835	3145	3415
40	1705	1990	2240	2485	2735	2950	3270	3550
30	1800	2095	2360	2620	2880	3105	3445	3740
10 LT	2095	2440	2745	3050	3355	3615	4010	4355
10 HT	1800	2095	2360	2620	2880	3105	3445	3740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.