


MULTIMAX MP 522

| | |
|---------------------|--|
| TIRE SIZE | 400/70 R 24 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 152 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|---|
| SW (MM) | 404 | RIM REC | 13 |
| OD (MM) | 1170 | RIM ALT | DW 12; 13 SDC; DW 13; DW 13 L; DW 14 L |
| SLR (MM) | 533 | ECE | E11-106R-002964 |
| RC (MM) | 3527 | SRI | 575 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|
| 50 | 1705 | 2025 | 2310 | 2630 | 2950 | 3160 | 3550 | - | - |
| 40 | 1705 | 2025 | 2310 | 2630 | 2950 | 3160 | 3550 | - | - |
| 30 | 1825 | 2170 | 2470 | 2815 | 3155 | 3385 | 3800 | - | - |
| 25 | 1895 | 2250 | 2565 | 2920 | 3275 | 3515 | 3945 | - | - |
| 10 CYC. | 2080 | 2560 | 3010 | 3465 | 3945 | 4290 | 4850 | 5115 | 5325 |
| STATIC | 3185 | 3920 | 4615 | 5310 | 6045 | 6575 | 7435 | 7840 | 8165 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.