

# EARTHMAX SR 55

<b>TIRE SIZE</b>	<b>18.00 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗОЧНО-ДОСТАВОЧНАЯ МАШИНА / ПОГРУЗЧИК
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	206 A2



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94515233	<b>RIM REC</b>	13.00/2.5
<b>OD (IN)</b>	65.6	<b>TRA CODE</b>	L5S
<b>SLR (IN)</b>	28.9	<b>STAR RATING</b>	★★★
<b>RC (IN)</b>	191.0		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
5	26000	26800	27600	28300	29100	30000	30900	32000	33100	33100	34200	35300	36400	36400	37500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.