

# SKID POWER HD (A)

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | 26X12 - 12         |
| <b>UM</b>           | IS STANDARD        |
| <b>CONSTRUCTION</b> | ❖ BIAS             |
| <b>MACHINERY</b>    | KOMPAKTHJULLASTARE |
| <b>VERSION</b>      | STANDARD           |
| <b>TIRE TYPE</b>    | TL                 |



## DIMENSIONER IS STANDARD

|                 |      |                |   |
|-----------------|------|----------------|---|
| <b>SW (MM)</b>  | 305  | <b>RIM REC</b> | 10.50 I - 55                                    |
| <b>OD (MM)</b>  | 660  | <b>RIM ALT</b> | 8.50 I - 55; 10.50 I - 70; 8½ JA; 9½ JA; 10½ JA |
| <b>SLR (MM)</b> | 297  | <b>ECE</b>     | E11-106R-004118                                 |
| <b>RC (MM)</b>  | 1947 | <b>PR</b>      | 8   |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.40</b> |
|-------------------|-------------|
| 10                | 1370        |
| 15                | 1080        |
| 25                | 1000        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.