

AGRIMAX V-FLECTO



AGRIMAX V-FLECTO
RADIAL VF TECHNOLOGY TIRES

AGRIMAX V-FLECTO



AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tyre is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tyres, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tyre. BKT has designed this tyre with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø18"	VF 280/70 R 18	116 D	W 9	9	10.8	33.4	14.8	99.0	400	STD
Ø28"	VF 600/60 R 28 NRO	157 D	DW 20 B	DW 18 L	23.1	56.7	24.9	166.5	675	STD
	VF 540/65 R 28 NRO	154 D	DW 20 B	DW 18 L	21.6	55.6	24.5	163.8	675	STD
	VF 520/60 R 28 NRO	149 D	DW 18 L	W 18 L	20.3	52.6	23.1	153.9	650	STD
	VF 480/60 R 28 NRO	145 D	DW 16 L	W 16 L	18.5	50.8	22.5	149.9	625	STD

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL




R1W




E 195 lbs

TECHNOLOGIES




PERFORMANCES








Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index



BKT AGRIMAX V-FLECTO
VF540/65 R30 & VF650/65 R42
Resources Protection
✓ Soil preservation
✓ Fuel saving
✓ User friendliness
✓ Soil discharge and self-cleaning
DLG Test Report 7444



SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
VF 600/70 R 28 NRO	167 D	DW 21 B	DW 20 B	23.7	61.1	26.1	180.9	725	STD
VF 600/65 R 28 NRO	163 D	DW 21 B	DW 20 B	23.5	58.7	25.8	175.3	700	STD
VF 340/85 R 28	139 D	W 12	W 11	14.0	50.8	22.5	150.9	625	STD
Ø30"	VF 710/60 R 30	171 D	DW 25 B DW 24 B DW 27 B	28.3	64.0	27.6	189.0	775	STD
	VF 600/70 R 30 NRO	168 D	DW 21 B	23.7	63.1	27.6	185.5	750	STD
	VF 600/60 R 30 NRO	158 D	DW 20 B	23.4	58.5	25.6	173.4	700	STD
	VF 540/65 R 30 NRO	158 D	DW 20 B	21.6	57.6	25.6	171.3	700	STD
	VF 480/70 R 30	153 D	W 18 L W 16 L DW 18 L	19.5	56.3	25.4	171.4	675	STD
Ø34"	VF 650/60 R 34	168 D	DW 23 B	26.0	66.0	29.5	196.7	775	STD
	VF 600/60 R 34	160 D	DW 20 B	23.4	62.4	27.2	185.4	750	STD

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL







TECHNOLOGIES



PERFORMANCES



Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index




SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
VF 600/70 R 34 NRO	170 D	DW 21 B	DW 20 B	23.7	67.1	29.1	197.8	800	STD
VF 710/55 R 34	170 D	DW 25 B	DW 27 B	27.9	65.3	28.6	193.3	775	STD
VF 710/60 R 34 NRO	173 D	DW 25 B	DW 24 B DW 27 B	27.9	67.6	29.6	200.7	825	STD
VF 480/70 R 34 NRO	166 D	W 18 L	W 16 L DW 18 L	19.5	62.2	27.9	186.6	750	STD
VF 650/65 R 34 NRO	170 D	DW 23 B	DW 21 B	25.6	67.3	29.8	201.2	825	STD
VF 600/65 R 34 NRO	169 D	DW 21 B	DW 20 B	23.5	64.7	28.8	195.0	775	STD
VF 540/65 R 38 NRO	162 D	DW 20 B	DW 18 L	21.6	66.0	29.9	196.1	800	STD
VF 650/60 R 38 NRO	173 D	DW 23 B	DW 21 B	25.6	68.7	30.5	205.4	825	STD
VF 650/65 R 38 NRO	169 D	DW 23 B	DW 21 B	25.6	71.3	31.4	212.1	875	STD
VF 710/55 R 38	175 D	DW 25 B	DW 24 B	28.0	68.9	30.7	206.4	825	STD

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL







TECHNOLOGIES



PERFORMANCES



Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index




SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
VF 650/75 R 38 NRO	175 D	DW 23 B	DW 21 B	26.6	76.4	32.8	228.2	925	STD
VF 600/60 R 38 NRO	168 D	DW 20 B	DW 18 L	23.1	66.3	29.8	199.9	800	STD
VF 650/60 R 38 NRO	166 D	DW 23 B	DW 21 B	25.6	68.7	30.5	205.9	825	STD
VF 710/70 R 38	181 D	DW 24 B	DW 23 B DW 25 B	28.1	77.2	33.2	227.3	925	STD
VF 480/80 R 38	166 D	DW 16 L	DW 15 L	18.9	68.2	30.5	203.5	825	STD
VF 650/85 R 38 CFO	182 D	DW 23 B	DW 20 B DW 21 B	26.4	81.5	34.9	240.9	975	SPL
VF 710/75 R 38	183 D	DW 24 B	DW 23 B DW 25 B	28.3	81.1	35.6	242.2	950	STD
VF 650/85 R 38	182 D	DW 23 B	DW 20 B DW 21 B	26.4	81.5	34.9	240.9	975	STD
VF 600/60 R 38 NRO	166 D	DW 20 B	DW 18 L	23.1	66.3	29.8	200.0	800	STD
VF 900/60 R 38 NRO	187 D	DW 30 B	-	34.7	80.5	34.7	238.3	975	STD

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL




R1W

E



195 lbs

TECHNOLOGIES



PERFORMANCES



Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index




SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
VF 520/70 R 38 CFO	164 D	DW 18 L	-	21.1	68.9	30.4	205.2	825	SPL
VF 710/60 R 38 NRO	171 D	DW 25 B	DW 23 B	27.9	71.7	31.3	214.4	875	STD
VF 800/70 R 38 CFO	187 D	DW 28 B	DW25 B DW27B DW30B	31.7	82.1	35.0	242.3	975	SPL
VF 520/70 R 38	164 D	DW 18 L	-	21.1	68.9	30.4	205.2	825	STD
Ø42"	VF 710/60 R 42 NRO	173 D	DW 25 B MW 25 B	28.0	76.0	33.9	227.8	925	STD
	VF 620/70 R 42	175 D	DW 21 B DW 23 B	24.4	76.2	33.4	228.1	925	STD
	VF 650/65 R 42 NRO	174 D	DW 23 B DW 21 B	25.6	75.3	33.5	227.3	925	STD
	VF 710/70 R 42	185 D	DW 25 B DW 23 B DW 24 B	28.1	81.1	36.3	243.4	975	STD
	VF 650/85 R 42 CFO	183 D	DW 23 B DW20B DW21B	26.8	85.0	36.9	252.5	1025	SPL
	VF 480/80 R 42	168 D	DW 16 L DW 15 L	18.9	72.4	32.5	215.2	875	STD

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL







TECHNOLOGIES



PERFORMANCES



Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index




SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
VF 520/85 R 42	180 D	DW 18 L	-	21.1	76.8	34.5	230.0	925	STD
VF 710/70 R 42 CFO	185 D	DW 25 B	DW 23 B DW 24 B	28.1	81.1	35.8	243.4	975	SPL
VF 580/85 R 42 CFO	183 D	DW20B	DW18B MW20B	23.9	81.0	36.3	242.8	975	SPL
VF 650/75 R 42 CFO	180 D	DW 23 B	DW 21 B	26.8	80.9	35.2	241.9	975	SPL
VF 650/60 R 42	174 D	DW 23 B	DW21B	26.0	72.6	32.8	219.1	875	STD
VF 900/60 R 42 NRO	189 D	DW 30B	-	35.4	84.3	36.9	251.6	1025	STD
VF 620/70 R 42 CFO	175 D	DW 21 B	DW 20 B DW 23 B	24.4	76.2	33.4	228.1	925	SPL
VF 710/70 R 42	193 D	DW 25 B	DW 23 B DW 24 B	28.3	81.0	36.5	245.4	975	SB
VF 900/60 R 42 CFO	195 D	DW 30B	-	35.4	84.3	37.2	252.4	1025	SB
VF 710/75 R 42	184 D	DW 24 B	DW 23 B DW 25 B	28.7	84.6	36.9	252.4	1000	STD

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL







TECHNOLOGIES



PERFORMANCES



Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index




	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	VF 900/60 R 42 CFO	189 D	DW 30B	-	35.4	84.3	36.7	251.6	1025	SPL
	VF 480/80 R 42 CFO	168 D	DW 16 L	DW 15 L	18.9	72.4	32.5	215.2	875	SPL
	VF 580/85 R 42 CFO	183 D	DW20B	DW18B MW20B	23.9	81.0	36.3	242.8	975	SPL
Ø44"	VF 750/70 R 44	186 D	DW 25 B	DW 24 B	29.9	85.6	37.7	253.9	1025	STD
Ø46"	VF 710/60 R 46 CFO	174 D	DW 25 B	DW 27 B	28.1	80.4	35.3	239.8	975	SPL
	VF 900/65 R 46	193 D	DW 30B	-	36.2	91.1	39.5	271.1	1100	STD
	VF 900/65 R 46 CFO	193 D	DW 30B	-	36.2	91.1	39.5	271.1	1100	SPL
	VF 900/65 R 46	193 D	DW 30B	-	35.4	92.0	39.6	275.7	1100	SB
	VF 710/60 R 46	174 D	DW 25 B	DW 27 B	28.1	80.4	35.3	239.8	975	STD
	VF 480/80 R 46 CFO	175 D	DW 16 L	DW 15 L	18.9	76.4	35.1	230.5	925	SB SPL

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL



R1W



E



195 lbs








Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index



BKT AGRIMAX V-FLECTO
VF340/65 R30 & VF650/65 R42
Resources Protection
✓ Soil preservation
✓ Fuel saving
✓ User friendliness
✓ Soil discharge and self-cleaning
DLG Test Report 7444



SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
VF 900/65 R 46 CFO	193 D	DW 30B	-	35.4	92.0	39.6	275.7	1100	SB SPL
VF 520/85 R 46	173 D	DW 18 L	-	21.1	80.8	35.9	240.6	975	STD
VF 580/85 R 46 CFO	179 D	DW 20 B	DW 21 B DW18L	23.8	84.9	37.3	254.0	1025	SPL
VF 710/65 R 46 NRO	188 E	DW 25 B	DW 23 B MW 25 B	28.93	82.28	37.14	248.42	975	STEEL BELTED SPECIAL
VF 710/65 R 46 NRO	188 E	DW 25 B	DW 23 B MW 25 B	28.93	82.28	37.14	248.42	975	SB
VF 480/80 R 50 CFO	179 D	DW16L	DW15L	18.9	80.2	36.9	243.9	975	SB SPL
VF 520/85 R 50 CFO	177 D	DW 18 L	DW 16 L	21.1	85.0	38.3	255.6	1025	SB SPL
VF 520/85 R 50	177 D	DW 18 L	DW 16 L	21.1	85.0	38.3	255.6	1025	SB

STD: STANDARD, SPL: SPECIAL, SB SPL: STEEL BELTED SPL, SB: STEEL BELTED, STEEL BELTED SPECIAL: STEEL BELTED SPECIAL







TECHNOLOGIES



PERFORMANCES



Permissible tolerances: 0.0-2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0, outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index


