


MULTIMAX MP 513

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | 325/70 R 18 MPT |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VEHICUL UNIVERSAL / CAMION PENTRU ÎNGRĂȘĂMINTE / VEHICUL UNIVERSAL |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 132 G |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 322 | RIM REC | W 10 |
| OD (MM) | 916 | ECE | E11-54R-0020959 |
| SLR (MM) | 410 | | |
| RC (MM) | 2771 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.5 | 3.0 | 3.5 |
|------------|------|------|------|------|------|
| 90 | 1095 | 1285 | 1530 | 1770 | 2000 |
| 65 | 1180 | 1390 | 1650 | 1915 | 2160 |
| 40 | 1255 | 1480 | 1760 | 2040 | 2300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.