


AGRIMAX TERIS

| | |
|---------------------|--|
| TIRE SIZE | IF 710/75 R 34 CFO |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / COTTON PICKER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 184 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94058723 | RC (IN) | 230.4 |
| SW (IN) | 28.2 | RIM REC | DW 25 B |
| OD (IN) | 76.0 | ECE | E11-106R-004899 |
| SLR (IN) | 34.3 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 |
|----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 7740 | 8930 | 10120 | 11510 | 12700 | 14090 | 15670 | 16860 | 18450 | 19840 |
| 25 | 7740 | 8930 | 10120 | 11510 | 12700 | 14090 | 15670 | 16860 | 18450 | 19840 |
| 20 | 8290 | 9560 | 10840 | 12320 | 13590 | 15080 | 16780 | 18050 | 19750 | 21230 |
| 10 CYC* | 12780 | 14740 | 16700 | 18990 | 20950 | 23250 | 25870 | 27830 | 30460 | 32740 |
| 5 CYC* | 13930 | 16070 | 18220 | 20720 | 22860 | 25360 | 28220 | 30360 | 33220 | 35710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.