

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>480/70 R 38</b>                                                              |
| <b>UM</b>        | IS STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | STANDARD                                                                        |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 145 D                                                                           |



## DIMENSIONES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 479  | <b>RIM REC</b> | W 15 L          |
| <b>OD (MM)</b>  | 1681 | <b>RIM ALT</b> | W 14 L ; W 16 L |
| <b>SLR (MM)</b> | 764  | <b>ECE</b>     | E11-106R-005832 |
| <b>RC (MM)</b>  | 5055 | <b>SRI</b>     | 800             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>65</b>    | 1595 | 1860 | 2120 | 2380 | 2640 | 2900 |
| <b>50</b>    | 1675 | 1950 | 2225 | 2500 | 2775 | 3045 |
| <b>40</b>    | 1750 | 2040 | 2325 | 2610 | 2895 | 3180 |
| <b>30</b>    | 1835 | 2135 | 2435 | 2735 | 3035 | 3335 |
| <b>10 LT</b> | 2140 | 2490 | 2840 | 3190 | 3540 | 3890 |
| <b>10 HT</b> | 1935 | 2135 | 2435 | 2735 | 3035 | 3335 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.