


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 600/70 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	165 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	603	<b>RIM REC</b>	DW 21 B; DW 21 A
<b>OD (MM)</b>	1602	<b>RIM ALT</b>	DW 20 A; DW 20 B
<b>SLR (MM)</b>	708	<b>ECE</b>	E11-106R-006495
<b>RC (MM)</b>	4800	<b>SRI</b>	750

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2200	2525	2900	3280	3650	4025	4400	4685
<b>FROM 65 TO 40</b>	2420	2780	3190	3605	4015	4425	4840	5150
<b>30</b>	2515	2890	3315	3745	4175	4600	5030	5355
<b>20</b>	2610	3000	3445	3890	4335	4775	5225	5560
<b>10</b>	3070	3530	4050	4575	5095	5615	6145	6540
<b>UPTO 30 CYC</b>	3145	3610	4145	4685	5215	5750	6290	6695
<b>UPTO 15 CYC</b>	3750	4305	4940	5585	6220	6855	7500	7980
<b>UPTO 10 CYC</b>	4110	4725	5420	6125	6825	7520	8225	8755
<b>10 HT</b>	2515	2890	3315	3745	4175	4600	5030	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.