

FLOTATION TR 675

TIRE SIZE	550/60 - 22.5
UM	US STANDARD
CONSTRUCTION	❖ BIAS
MACHINERY	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	167 A8/163 B



РАЗМЕРЫ US STANDARD

USA CODE	94019816	RC (IN)	143.3
SW (IN)	21.7	RIM REC	AG 16.00
OD (IN)	49.6	ECE	E11-106R-004397
SLR (IN)	21.5	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	35	38	41
5 FR	15370	16110	16820
10 FR	13830	14490	15130
20 FR	12300	12890	13460
25 FR	10980	11510	12010
30 FR	9880	10360	10750
5 DW	10570	11080	11570
10 DW	9510	9980	10420
20 DW	8450	8860	9260
25 DW	7550	7910	8270
30 DW	6800	7120	7390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.