


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 620/75 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94064717	<b>RC (IN)</b>	200.8
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	67.0	<b>RIM ALT</b>	DW 21 B
<b>SLR (IN)</b>	29.9	<b>ECE</b>	E11-106R-006496

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5460	6270	7210	8130	9060	10000	10920	11630
<b>FROM 40 TO 25</b>	6010	6900	7930	8950	9960	10990	12010	11355
20	6240	7180	8230	9300	10360	11420	12490	13290
12	6480	7450	8550	9660	10760	11860	12970	13800
5	7630	8760	10060	11360	12650	13950	15260	16240
<b>UPTO 20 CYC</b>	7800	8960	10300	11630	12950	14290	15620	16620
<b>UPTO 10 CYC</b>	9300	10690	12280	13870	15440	17030	18620	19820
<b>UPTO 5 CYC</b>	10210	11730	13470	15210	16930	18670	20420	21740
5 HT	6240	7180	8230	9300	10360	11420	12490	13290

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.