

FLOTATION TR 675

TIRE SIZE	500/60 - 22.5
UM	US STANDARD
CONSTRUCTION	❖ BIAS
MACHINERY	MAQUINARIA AGRÍCOLA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	155 A8/151 B
LI/SS FREE ROLLING	168 A8/164 B



DIMENSIONES US STANDARD

CÓDIGO USA	94050147	RC (IN)	141.9
SW (IN)	20.3	RIM REC	AG 16.00
OD (IN)	46.5	RIM ALT	15.00; 17.00
SLR (IN)	21.3	ECE	E11-106R-004395

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54	55	58
5 FR	16370	16630	17280
10 FR	14740	14970	15550
20 FR	13090	13300	13820
25 FR	11690	11880	12350
30 FR	10530	10690	11020
5 DW	11580	11770	11960
10 DW	10430	10590	10770
20 DW	9270	9420	9570
25 DW	8280	8410	8540
30 DW	7450	7570	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.