

# TR 678

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 600/65 - 34  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ MAQUINARIA AGRÍCOLA /<br>AUTOCARGADORA / PALA<br>EXCAVADORA / REMOLQUE |
| <b>VERSIÓN</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 164 A2 ; 160 A6  |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94032679 | <b>RC (IN)</b> | 193.5           |
| <b>SW (IN)</b>    | 24.0     | <b>RIM REC</b> | DW 20 B         |
| <b>OD (IN)</b>    | 64.7     | <b>ECE</b>     | E11-106R-003648 |
| <b>SLR (IN)</b>   | 29.8     | <b>PR</b>      | 14              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>35</b> |
|------------------|-----------|
| 20               | 9920      |
| 5                | 11020     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.