


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 520/85 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 167 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------------------------|
| USA CODE | 94060139 | RC (IN) | 227.6 |
| SW (IN) | 20.3 | RIM REC | DW 16 L ; W 16 A ; DD 16 |
| OD (IN) | 76.8 | RIM ALT | DW 18 A ; DD 18 ; W 18 A ; DD 18 L |
| SLR (IN) | 33.8 | ECE | E4-106R-001491 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 35 | 41 | 46 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|
| 30 | 5000 | 5820 | 6650 | 7460 | 8280 | 9090 | 10220 | 11180 | 12010 |
| 25 | 5000 | 5820 | 6650 | 7460 | 8280 | 9090 | 10220 | 11180 | 12010 |
| 20 | 5360 | 6240 | 7110 | 7990 | 8860 | 9730 | 10930 | 11960 | 12850 |
| 5 LT | 6710 | 7800 | 8910 | 10000 | 11100 | 12190 | 13690 | 14980 | 16100 |
| 5 HT | 5360 | 6240 | 7110 | 7990 | 8860 | 9730 | 10930 | 11960 | 12850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.