

# TR 117

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>11.2 - 38</b>                                  |
| <b>UM</b>           | IS STANDARD                                       |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | EQUIPO DE RIEGO A PIVOTE /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 109 A6  |



## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 284  | <b>RIM REC</b> | W 10           |
| <b>OD (MM)</b>  | 1445 | <b>RIM ALT</b> | W 9            |
| <b>SLR (MM)</b> | 675  | <b>ECE</b>     | E4-106R-002747 |
| <b>RC (MM)</b>  | 4400 | <b>PR</b>      | 4              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>1.30</b> | <b>1.70</b> |
|-------------------|-------------|-------------|
| <b>30</b>         | 1030        | ---         |
| <b>CREEP</b>      | ---         | 2005        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.