



IS standard



GROWING TOGETHER

SNOW - EXCEL



PRODUCT DATA SHEET



Bias



149

Performance



Ice and Snow



Road Oriented



Traction



SNOW - EXCEL

🇬🇧 SNOW-EXCEL is particularly suitable for industrial and construction applications on the road in winter conditions. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

| | Tire size | Type | PR | LI/SS | Version | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | RIM | |
|-------|-----------|------|----|-------|---------|--------------|--------------|-------------|------------|-----------|---------|
| | | | | | | | | | | Rec. | Alt. |
| Ø 24" | 16.9 - 24 | - | 10 | - | STD | 445 | 1320 | 607 | 3978 | DW 15 L | DW 14 L |
| | 16.9 - 24 | TL | 12 | 149A8 | STD | 445 | 1320 | 601 | 3971 | DW 15 L | DW 14 L |
| Ø 25" | 17.5 - 25 | TL | 12 | - | STD | 445 | 1370 | 612 | 4070 | 14.00/1.5 | - |
| | 20.5 - 25 | TL | 16 | - | STD | 524 | 1490 | 657 | 4434 | 17.00/2.0 | - |
| | 23.5 - 25 | TL | 16 | - | STD | 600 | 1620 | 692 | 4787 | 19.50/2.5 | - |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference