


# AGRIMAX RT 955

<b>TYRE SIZE</b>	<b>210/90 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	107 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94042531	<b>RC (IN)</b>	119.2
<b>SW (IN)</b>	8.4	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	39.8	<b>RIM ALT</b>	W 6
<b>SLR (IN)</b>	18.2	<b>ECE</b>	E4-106R-001818

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
30	1010	1170	1330	1510	1690	1850	2010	2150	-
25	1010	1170	1330	1510	1690	1850	2010	2150	-
20	1090	1250	1430	1620	1810	1980	2150	2300	-
5	1490	1720	1910	2110	2330	2560	2980	3140	3230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.