


# AGRIMAX V- FLECTO

TIRE SIZE	VF 800/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	SPECIAL
TIRE TYPE	TL
LI/SS	187 D



## DIMENSÕES IS STANDARD

SW (MM)	804	RIM REC	DW 28 B
OD (MM)	2085	RIM ALT	DW25 B; DW27B; DW30B
SLR (MM)	890	ECE	E11-106R-007205
RC (MM)	6155	SRI	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	4440	5150	5860	6660	7370	8080	8875
FROM 65 TO 40	4875	5655	6435	7315	8095	8875	9750
30	4975	5770	6565	7460	8255	9050	9945
20	5070	5885	6695	7605	8420	9230	10140
10	5365	6225	7080	8045	8905	9760	10725
UPTO 30 CYC	5535	6420	7305	8305	9190	10075	11067
UPTO 15 CYC	6610	7665	8720	9910	10970	12025	13212
UPTO 10 CYC	7240	8400	9560	10860	12020	13180	14479
10 HT	4975	5770	6565	7460	8255	9050	9945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.