

AGRIMAX RT 765M

| | |
|---------------------|---|
| TIRE SIZE | 710/70 R 42 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 173 D ; 176 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94066476 | RC (IN) | 243.1 |
| SW (IN) | 28.2 | RIM REC | DW 23 B |
| OD (IN) | 81.1 | RIM ALT | DW 25 B |
| SLR (IN) | 36.3 | ECE | E11-106R-006018 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 6730 | 7740 | 8880 | 10030 | 11180 | 12320 | 13470 | 14330 |
| 30 | 7080 | 8130 | 9340 | 10540 | 11740 | 12940 | 14150 | 15050 |
| 25 | 7390 | 8480 | 9730 | 10990 | 12250 | 13500 | 14760 | 15700 |
| 15 | 7750 | 8910 | 10220 | 11540 | 12860 | 14170 | 15500 | 16480 |
| 5 LT | 9030 | 10370 | 11920 | 13450 | 14980 | 16520 | 18050 | 19200 |
| 5 HT | 7750 | 8910 | 10220 | 11540 | 12860 | 14170 | 15500 | 16480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.