

AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 230/95 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 128 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 228 | RIM REC | W 7 |
| OD (MM) | 1251 | RIM ALT | W 8 |
| SLR (MM) | 585 | ECE | E4-106R-000764 |
| RC (MM) | 3810 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50 | 705 | 920 | 1120 | 1225 | 1300 | 1425 | 1550 | 1675 | 1800 | - |
| 40 | 705 | 920 | 1120 | 1225 | 1300 | 1425 | 1550 | 1675 | 1800 | - |
| 30 | 755 | 985 | 1200 | 1315 | 1390 | 1525 | 1660 | 1795 | 1930 | - |
| 10 | 840 | 1055 | 1300 | 1540 | 1785 | 1840 | 2055 | 2270 | 2485 | 2700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.