

FLOTATION 648

| | |
|---------------------------|----------------------------|
| TYRE SIZE | 850/50 - 30.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | HAY HARVESTER / IMPLEMENTS |
| VERSION | HD |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 176 A8/173 B |
| LI/SS FREE ROLLING | 189 A8/185 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94030286 | RC (IN) | 194.3 |
| SW (IN) | 33.5 | RIM REC | AG 28.00 |
| OD (IN) | 65.0 | ECE | E11-106R-004566 |
| SLR (IN) | 28.0 | PR | 18 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 33 | 34 | 36 |
|--------------|-------|-------|-------|
| 5 FR | 30280 | 31030 | 31790 |
| 10 FR | 27250 | 27930 | 28610 |
| 20 FR | 24220 | 24820 | 25430 |
| 25 FR | 21630 | 22170 | 22710 |
| 30 FR | 19470 | 19950 | 20390 |
| 5 DW | 20870 | 21380 | 21910 |
| 10 DW | 18780 | 19250 | 19720 |
| 20 DW | 16690 | 17110 | 17530 |
| 25 DW | 14900 | 15280 | 15650 |
| 30 DW | 13410 | 13750 | 14330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.