


AGRIMAX V-FLECTO

TIRE SIZE	VF 480/80 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL



DIMENSIONES US STANDARD

CÓDIGO USA	94517022	RC (IN)	215.2
SW (IN)	18.9	RIM REC	DW 16 L
OD (IN)	72.4	RIM ALT	DW 15 L
SLR (IN)	32.5	ECE	E11-106R-0010410

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5280	6070	6970	7870	8760	9670	10560	11230
FROM 40 TO 25	5810	6670	7660	8640	9630	10630	11610	12350
20	5920	6800	7810	8820	9820	10840	11840	12590
12	6040	6930	7960	8980	10010	11040	12070	12830
5	6390	7340	8420	9510	10590	11680	12780	13580
UPTO 5 CYC	8130	9335	10725	12095	13485	14875	16245	17280
5 HT	5920	6800	7810	8820	9820	10840	11840	12590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.