

# ROCK GRIP E4

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>18.00 - 25</b> |
| <b>UM</b>           | US STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK  |
| <b>VERSION</b>      | STANDARD          |
| <b>TIRE TYPE</b>    | TT                |



## DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94015474 | <b>RIM REC</b>  | 13.00/2.5 |
| <b>OD (IN)</b>  | 65.0     | <b>RIM ALT</b>  | 15.00/2.5 |
| <b>SLR (IN)</b> | 29.6     | <b>PR</b>       | 24        |
| <b>RC (IN)</b>  | 192.3    | <b>TRA CODE</b> | E4        |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 62    | 80    |
|-----------|-------|-------|
| 30        | 16100 | -     |
| 5         | -     | 27600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.