


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>380/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	132 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	380	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1082	<b>RIM ALT</b>	W 11 ; W 13
<b>SLR (MM)</b>	482	<b>ECE</b>	E4-106R-00648
<b>RC (MM)</b>	3213	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	940	1080	1240	1400	1560	1720	1860	2000
40	940	1080	1240	1400	1560	1720	1860	2000
30	1010	1160	1330	1500	1670	1845	1995	2140
10 LT	1260	1450	1665	1880	2095	2305	2495	2680
10 HT	1010	1160	1330	1500	1670	1845	1995	2140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.