


# RIDEMAX IT 696

<b>TYRE SIZE</b>	<b>360/80 R 20 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	143 D ; 147 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	357	<b>RIM REC</b>	11
<b>OD (MM)</b>	1084	<b>RIM ALT</b>	W 10; W 11; 12; W 12
<b>SLR (MM)</b>	488	<b>ECE</b>	E11-106R-007845
<b>RC (MM)</b>	3235	<b>SRI</b>	525

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1310	1585	1885	2100	2180	2265	2480	2725
50	1415	1710	2035	2270	2360	2445	2680	2945
40	1480	1785	2125	2370	2460	2555	2800	3075
30	1570	1900	2260	2520	2620	2715	2980	3270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.