


# AS 511

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>33X15.50 R 15</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | OUTILLAGE AGRICOLE / OUTILLAGE AGRICOLE  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 126 B  |



## DIMENSIONS IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 404  | <b>RIM REC</b> | 13 LB            |
| <b>OD (MM)</b>  | 840  | <b>ECE</b>     | E11-106R-0010516 |
| <b>SLR (MM)</b> | 375  | <b>SRI</b>     | 400              |
| <b>RC (MM)</b>  | 2533 |                |                  |

## LOAD CAPACITY (KG/TIRE)

|                   |            |
|-------------------|------------|
| <b>KM/H / BAR</b> | <b>2.8</b> |
| 50                | 1700       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.