


AGRIMAX TERIS

| | |
|---------------------|--|
| TIRE SIZE | 800/65 R 32 CHO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER / PAMUK TOPLAMA MAKINESİ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 178 A8 ; 175 B |



BOYUTLAR IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------|
| SW (MM) | 818 | RIM REC | DW 27 B |
| OD (MM) | 1853 | RIM ALT | DW 25 B ; DH 27 B |
| SLR (MM) | 838 | ECE | E4-106R-001430 |
| RC (MM) | 5551 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|-------|-------|-------|-------|
| 50 | 3175 | 3660 | 4485 | 4900 | 5455 | 5865 | 6420 | 6900 |
| 40 | 3450 | 3975 | 4875 | 5325 | 5925 | 6375 | 6975 | 7500 |
| 30 | 3695 | 4255 | 5220 | 5700 | 6340 | 6825 | 7465 | 8025 |
| 15 CYC | 5695 | 6560 | 8045 | 8790 | 9780 | 10520 | 11510 | 12375 |
| 10 CYC | 6210 | 7155 | 8775 | 9585 | 10665 | 11475 | 12555 | 13500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.