

# TR 882

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA / REMOLQUE
<b>VERSIÓN</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	132 A8
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	AG 13.00
<b>OD (MM)</b>	875	<b>ECE</b>	E4-106R-001879
<b>SLR (MM)</b>	378	<b>PR</b>	14
<b>RC (MM)</b>	2605	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.60</b>
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2800
25 DW	2380
30 DW	2240
40 DW	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.