

# AS 504

<b>TIRE SIZE</b>	15.0/55 - 17
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	128 A8
<b>LI/SS FREE ROLLING</b>	141 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	380	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	890	<b>RIM ALT</b>	13
<b>SLR (MM)</b>	395	<b>ECE</b>	E4-106R-001572
<b>RC (MM)</b>	2608	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575
10 DW	2520
25 DW	2140
30 DW	2010
40 DW	1800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.