


AGRIMAX V- FLECTO



TIRE SIZE	VF 650/65 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	169 D

DIMENSIONI IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1811	RIM ALT	DW 21 B
SLR (MM)	798	ECE	E11-106R-005022
RC (MM)	5387	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2950	3480	3955	4430	4850	5275
FROM 65 TO 40	3245	3825	4350	4870	5335	5800
30	3305	3900	4435	4965	5440	5915
20	3370	3975	4520	5060	5545	6030
10	3565	4205	4785	5355	5865	6380
*UPTO 10 CYC WITH FRONT LOADER	4540	5355	6090	6815	7465	8120
10HT	3305	3900	4435	4965	5440	5915

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.