

# SNOW - EXCEL

|                     |             |
|---------------------|-------------|
| <b>TIRE SIZE</b>    | 16.9 - 24   |
| <b>UM</b>           | IS STANDARD |
| <b>CONSTRUCTION</b> | ⊠ BIAS      |
| <b>MACHINERY</b>    | TRACTOR     |
| <b>VERSIÓN</b>      | STANDARD    |
| <b>TIRE TYPE</b>    | TL          |
| <b>LI/SS</b>        | 149 A8      |



## DIMENSIONES IS STANDARD

|                 |      |                |         |
|-----------------|------|----------------|---------|
| <b>SW (MM)</b>  | 445  | <b>RIM REC</b> | DW 15 L |
| <b>OD (MM)</b>  | 1320 | <b>RIM ALT</b> | DW 14 L |
| <b>SLR (MM)</b> | 601  | <b>PR</b>      | 12      |
| <b>RC (MM)</b>  | 3971 | <b>SRI</b>     | 625     |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.60</b> |
| 40                | 3250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.