


# AGRIMAX PROCROP

<b>TYRE SIZE</b>	<b>VF 320/90 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>VERSION</b>	STEEL BELTED
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	165 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	323	<b>RIM REC</b>	DW11
<b>OD (MM)</b>	1750	<b>RIM ALT</b>	W11;DW10
<b>SLR (MM)</b>	817	<b>ECE</b>	E11-106R-0011308
<b>RC (MM)</b>	5345	<b>SRI</b>	825

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
<b>70</b>	2050	2290	2575	2815	2955	3100	3195	3290	3455	3625	3765	3910	4030	4150	4265	4385	4575	4765
<b>FROM 65 TO 40</b>	2215	2475	2785	3040	3195	3350	3455	3555	3735	3915	4070	4225	4355	4485	4610	4740	4945	5150
<b>30</b>	2260	2525	2840	3105	3260	3420	3525	3630	3810	3995	4155	4310	4445	4575	4705	4835	5045	5255
<b>20</b>	2305	2575	2895	3165	3325	3485	3595	3700	3890	4075	4235	4400	4530	4665	4800	4935	5150	5360
<b>10*</b>	2440	2720	3060	3345	3515	3685	3800	3910	4110	4310	4480	4650	4790	4930	5075	5215	5440	5665
<b>UPTO 15 CYC.</b>	3005	3355	3770	4120	4330	4540	4680	4820	5065	5305	5515	5725	5900	6075	6250	6425	6705	6980
<b>UPTO 30 CYC.</b>	2520	2810	3160	3455	3630	3805	3920	4040	4245	4450	4625	4800	4945	5090	5240	5385	5620	5850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.