

# AGRIMAX RT 765

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>260/70 R 16</b>                                                                       |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / LANDWIRTSCHAFTLICHE<br>GERÄTE / TRAUBENERNTEMASCHINE<br>/ ERNTEMASCHINE        |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 109 A8/B                                                                                 |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 258  | <b>RIM REC</b> | W 8            |
| <b>OD (MM)</b>  | 770  | <b>RIM ALT</b> | W 8 L ; W 9 L  |
| <b>SLR (MM)</b> | 346  | <b>ECE</b>     | E4-106R-000610 |
| <b>RC (MM)</b>  | 2283 | <b>SRI</b>     | 370            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6 | 0.8 | 1.0 | 1.2 | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|-----|-----|-----|-----|------|------|------|------|
| <b>50</b>    | 485 | 560 | 640 | 725 | 805  | 890  | 960  | 1030 |
| <b>40</b>    | 485 | 560 | 640 | 725 | 805  | 890  | 960  | 1030 |
| <b>30</b>    | 520 | 600 | 690 | 775 | 865  | 955  | 1030 | 1105 |
| <b>10 LT</b> | 650 | 750 | 860 | 970 | 1080 | 1190 | 1285 | 1380 |
| <b>10 HT</b> | 520 | 600 | 690 | 775 | 865  | 955  | 1030 | 1105 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.