


AGRIMAX FORCE

TIRE SIZE	IF 600/70 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	164 D



DIMENSIONER US STANDARD

USA CODE	94044689	RC (IN)	183.2
SW (IN)	23.7	RIM REC	DW 21 B
OD (IN)	61.1	RIM ALT	DW 20 B
SLR (IN)	27.3	ECE	E4-106R-000795

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4710	5410	6220	7020	7810	8620	9420	10030
FROM 40 TO 25	5180	5950	6830	7720	8600	9480	10360	11000
20	5380	6180	7100	8020	8940	9850	10770	11460
12	5590	6430	7370	8330	9280	10230	11190	11900
5	6570	7550	8670	9800	10910	12040	13150	14000
*UPTO 5 CYC WITH FRONT LOADER	7250	8330	9570	10800	12040	13270	14510	15430
5 HT	5380	6180	7100	8020	8940	9850	10770	11460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.