


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>250/85 R 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / IMPLEMENTS / VINEYARD<br>HARVESTER / HARVESTER                                 |
| <b>VERSION</b>      | SPECIAL  |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 109 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94046751 | <b>RC (IN)</b> | 122.2          |
| <b>SW (IN)</b>  | 9.9      | <b>RIM REC</b> | W 8            |
| <b>OD (IN)</b>  | 40.8     | <b>RIM ALT</b> | W 7 ; W 9      |
| <b>SLR (IN)</b> | 18.7     | <b>ECE</b>     | E4-106R-000638 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 1260 | 1450 | 1660 | 1860 | 2070 | 2270 |
| 25        | 1260 | 1450 | 1660 | 1860 | 2070 | 2270 |
| 20        | 1340 | 1570 | 1790 | 2010 | 2230 | 2440 |
| 5 LT      | 1690 | 1960 | 2240 | 2510 | 2790 | 3050 |
| 5 HT      | 1340 | 1570 | 1790 | 2010 | 2230 | 2440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.