

FL 630 SUPER

TIRE SIZE	560/60 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D



РАЗМЕРЫ US STANDARD

USA CODE	94059539	RC (IN)	149.0
SW (IN)	21.4	RIM REC	AG 16.00
OD (IN)	49.0	RIM ALT	17.00; 20.00
SLR (IN)	21.6	ECE	E11-106R-006945

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58	73
45	3430	3850	4780	5430	6280	7120	7780	8530	9370	10470
40	3730	4190	5200	5920	6830	7750	8470	9280	10200	11350
30	4520	5070	6300	7160	8280	9390	10250	11240	12350	13750
25	5070	5690	7080	8050	9290	10550	11520	12620	13870	15440
15	5890	6610	8220	9350	10800	12260	13380	14670	16110	17940
5	6700	7530	9370	10650	12300	13950	15230	16710	18350	20440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.