


AS 504

TIRE SIZE	11.5/80 - 15.3
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8



РАЗМЕРЫ US STANDARD

USA CODE	94018765	RC (IN)	100.0
SW (IN)	11.4	RIM REC	9.00
OD (IN)	34.1	ECE	E11-106R-003510
SLR (IN)	15.0	PR	14

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.