


RIDEMAX IT 696

| | |
|---------------------|--|
| TYRE SIZE | 360/80 R 20 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 143 D ; 147 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------------|
| USA CODE | 94071074 | RC (IN) | 127.4 |
| SW (IN) | 14.1 | RIM REC | 11 |
| OD (IN) | 42.7 | RIM ALT | W 10 ; W 11 ; 12 ; W 12 |
| SLR (IN) | 19.2 | ECE | E11-106R-007845 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2890 | 3490 | 4160 | 4630 | 4810 | 4990 | 5470 | 6010 |
| 30 | 3120 | 3770 | 4490 | 5000 | 5200 | 5390 | 5910 | 6490 |
| 25 | 3260 | 3940 | 4680 | 5220 | 5420 | 5630 | 6170 | 6780 |
| 20 | 3460 | 4190 | 4980 | 5560 | 5780 | 5990 | 6570 | 7210 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.