


# EARTHMAX SR 31

|                     |                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>23.5 R 25</b>                                                                            |
| <b>UM</b>           | US STANDARD                                                                                 |
| <b>CONSTRUCTION</b> |  RADIAL    |
| <b>MACHINERY</b>    | CARREGADORA / TRATOR DE ESTEIRA<br>/ DUMPER ARTICULADO /<br>CARREGADORA / TRATOR DE ESTEIRA |
| <b>VERSÃO</b>       | CUT RESISTANT COMPOUND                                                                      |
| <b>TIRE TYPE</b>    | TL                                                                                          |
| <b>LI/SS</b>        | 185 B ; 195 A2                                                                              |



## DIMENSÕES US STANDARD

|                   |          |                    |           |
|-------------------|----------|--------------------|-----------|
| <b>CÓDIGO USA</b> | 94048434 | <b>RIM REC</b>     | 19.50/2.5 |
| <b>OD (IN)</b>    | 63.3     | <b>TRA CODE</b>    | E3/L3     |
| <b>SLR (IN)</b>   | 28.0     | <b>STAR RATING</b> | ★★/★      |
| <b>RC (IN)</b>    | 188.9    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 16500 | 17100 | 18200 | 18700 | 19800 | 20400 |
| 5         | 22700 | 23400 | 24700 | 25400 | 26800 | --    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.