DATA SHEET

PRINTED ON

MULTIMAX MP 525

TIRE SIZE	**455/70 R 24**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	UNIVERSELLES FAHRZEUG / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER / PLANIERER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	154 G ; 154 B ; 165 A2

ABMESSUNGEN IS STANDARD

OD (MM)	1250	**RIM ALT**	13; DW14L
SLR (MM)	571	**ECE**	E11-54R-0021226
RC (MM)	3794		
RIM REC	14		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	3.75
90	3750	-
50	-	3750
10	-	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..