


# EARTHMAX SR 30

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>23.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK / DOZER   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 185 B ; 195 A2   |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94026715 | <b>RIM REC</b>     | 19.50/2.5 |
| <b>OD (IN)</b>  | 63.3     | <b>TRA CODE</b>    | E3/L3     |
| <b>SLR (IN)</b> | 28.0     | <b>STAR RATING</b> | ★★★       |
| <b>RC (IN)</b>  | 188.9    |                    |           |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 16500 | 17100 | 18200 | 18700 | 19800 | 20400 |
| 5         | 22700 | 23400 | 24700 | 25400 | 26800 | -     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.