

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>480/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTAT PODGORII / RECOLTAREA LIVEZILOR / TRACTOR MIC / TRACTOR / MAȘINĂ DE RECOLTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	141 A8 ; 141 B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94075409	<b>RC (IN)</b>	173.1
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	58.2	<b>RIM ALT</b>	W 14 L ; W 16 L
<b>SLR (IN)</b>	26.0	<b>ECE</b>	E11-106R-009050

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	3140	3640	4150	4670	5170	5680
25	3140	3640	4150	4670	5170	5680
20	3360	3910	4450	5000	5550	6090
5 LT	4200	4890	5570	6250	6940	7620
5 HT	3360	3910	4450	5000	5550	6090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.