


# PL 801

<b>TIRE SIZE</b>	<b>6.50 - 10</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	RASTRILLO HILERADOR ROTATIVO / COSECHADORA / CARRETILLA ELEVADORA / COSECHADORA / MAQUINARIA AGRÍCOLA / CARRETILLA ELEVADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94007165	<b>RIM ALT</b>	5.50 F
<b>SW (IN)</b>	7.3	<b>ECE</b>	E11-106R-003566
<b>OD (IN)</b>	23.4	<b>PR</b>	10
<b>RIM REC</b>	5.00 F		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	112
15 LOAD WHEEL	4300
15 STEER WHEEL	3305
5 OTHER VEHICLES	4300
15 OTHER VEHICLES	3305
STATIC SIDE LOADER	4995

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.