

# AW 09

<b>TIRE SIZE</b>	<b>260/70 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ARBETSFORDON / SLÄPVAGN / BALPRESS / SKÖRDEMASKIN / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	110 A8
<b>LI/SS FREE ROLLING</b>	122 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94037858	<b>RC (IN)</b>	86.9
<b>SW (IN)</b>	10.6	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	29.6	<b>ECE</b>	E4-106R-000372
<b>SLR (IN)</b>	13.2		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	4630
15 FR	3940
20 FR	3700
25 FR	3310
5 DW	3270
15 DW	2780
20 DW	2610
25 DW	2340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.