


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>420/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	144 A8/B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94034512	<b>RC (IN)</b>	202.2
<b>SW (IN)</b>	17.2	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	68.3	<b>RIM ALT</b>	W 13 ; W 14 L
<b>SLR (IN)</b>	30.9	<b>ECE</b>	E4-106R-000780

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	3390	3960	4510	5070	5620	6160
25	3390	3960	4510	5070	5620	6160
20	3640	4230	4830	5420	6020	6610
5 LT	4560	5300	6050	6790	7540	8280
5 HT	3640	4230	4830	5420	6020	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.