


# EARTHMAX SR 53

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>45/65 R 45</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / LOADER / LOW PROFILE<br>DUMP TRUCK   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 250 A2   |



## DIMENSIONS IS STANDARD

|                 |           |                    |     |
|-----------------|-----------|--------------------|-----|
| <b>OD (MM)</b>  | 2730      | <b>TRA CODE</b>    | L5  |
| <b>SLR (MM)</b> | 1211      | <b>STAR RATING</b> | ★★★ |
| <b>RC (MM)</b>  | 8224      |                    |     |
| <b>RIM REC</b>  | 36.00/4.5 |                    |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 7.00  | 7.50  | 8.00  |
|------------|-------|-------|-------|
| 10         | 54500 | 56000 | 60000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.