



US standard



GROWING TOGETHER

TR 136



PRODUCT DATA SHEET



Bias



Technologies



Special Compound



More Lugs

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Traction



TR 136

TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and haulage operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity. Thanks to the increased number of lugs, TR 136 provides outstanding traction even at high loads.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 26"	94039906	18.4 - 26	W 16 L	W 15 L	18.9	57.1	25.4	165.6	52	215	SPL	12	TL	142 A8
	94046294	18.4 - 26	W 16 L	W 15 L	18.9	57.1	25.4	165.6	52	217	STD	14	TL	146 A8
	94004218	18.4 - 26	W 16 L	W 15 L	18.9	57.1	25.4	165.6	52	208	STD	12	TL	142 A8
	94026265	18.4 - 26	W 16 L	W 15 L	18.9	57.1	25.4	165.6	52	203	STD	12	TT	142 A8
Ø 28"	94036417	12.4 - 28	W 11	W 9; W 10	12.4	50.2	23.4	147.6	42	99	STD	8	TT	120 A8
Ø 30"	94028276	16.9 - 30	W 15 L	W 14 L	16.9	58.5	26.7	175.4	47	180	HD	8	TT	132 A8
	94048755	16.9 - 30	W 15 L	W 14 L	16.9	58.5	27.0	178.1	47	198	SPL	12	TL	140 A8
	94004225	16.9 - 30	W 15 L	W 14 L	16.9	58.5	26.7	175.4	47	171	SPL	8	TT	132 A8
	94004232	16.9 - 30	W 15 L	W 14 L	16.9	58.5	27.0	178.1	47	191	SPL	12	TT	140 A8
	94044108	16.9 - 30 (14 - 30)	W 15 L	W 14 L	16.9	58.5	26.7	175.4	47	180	STD	14	TT	143 A8
	94004188	16.9 - 30	W 15 L	W 14 L	16.9	58.5	26.7	175.4	47	177	STD	8	TT	132 A8
	94004195	16.9 - 30	W 15 L	W 14 L	16.9	58.5	26.7	175.4	47	181	STD	10	TT	136 A8
	94004201	16.9 - 30	W 15 L	W 14 L	16.9	58.5	27.0	178.1	47	163	STD	12	TT	140 A8
	94029259	18.4 - 30	W 16 L	W 15 L	18.4	61.0	28.0	185.8	52	226	HD	8	TT	135 A8
	94029129	18.4 - 30	W 16 L	W 15 L	18.4	61.0	28.0	185.8	52	245	HD	12	TT	145 A8
	94004133	18.4 - 30	W 16 L	W 15 L	18.4	61.0	28.0	185.8	52	257	HD	14	TT	147 A8
	94004300	18.4 - 30	W 16 L	W 15 L	18.4	61.0	28.0	185.8	52	229	SPL	12	TT	145 A8
	94027514	18.4 - 30	W 16 L	W 15 L	18.4	61.0	28.0	185.8	52	219	STD	8	TT	135 A8

SPL: Special - STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference